

HALFEN HLX Lift-Box: THE STRENGTH BEHIND LIFT INSTALLATION

NEW



YOUR BEST CONNECTIONS

All features at a glance:



› CE marking with European Technical Assessment



› Additional load steps:
2000 kg and 4000 kg



› Chain-link as attachment point:
Automatic release and self-locking

The new generation: STRONGER WITH NEW LOAD STEPS



The new generation of the HALFEN HLX Lift-Box will be available from January 2019. Two new load steps and a new design complement the HALFEN product range of attachment points for installation and maintenance of lifts.

HLX LIFT-BOX

Application: Installation and maintenance work in lift shafts. The increasing importance of scaffold-free lift installation in lift shafts requires attachment points cast in the ceiling of concrete shafts for temporary attachment of various loads.

The HALFEN HLX Lift-Box ensures reliable, safe, temporary attachment of hoisting apparatus, speed governor/limiter, motor and other equipment during installation or maintenance of the lift.

EASY INSTALLATION

The HALFEN HLX Lift-Box is delivered to site as a ready-to install solution. It is used for the transmission of predominantly static loads. Rotation locking guaranteed. Due to its low overall height, it can be used in slab thicknesses from as little as 150 mm.

NEW LOAD CLASSES						
Type	Load attachment method	Load class	Permissible weight	Installation height h_{nom}	Component thickness min h	Minimum concrete strength
HLX15 Loop	Loop	1.5	1500 kg	133.0 mm	150 mm	C25/30
HLX20 Loop	Loop	2.0	2000 kg	139.5 mm	150 mm	C25/30
HLX20 Link	Chain-link	2.0	2000 kg	139.0 mm	150 mm	C25/30
HLX40 Link	Chain-link	4.0	4000 kg	209.5 mm	220 mm	C25/30

HALFEN GmbH

Liebigstr. 14 · 40764 Langenfeld · GERMANY

Phone: +49 (0)2173 / 970-9061

Fax: +49 (0)2173 / 970-427

E-Mail: info@halfen.com

www.halfen.com

The Quality Management System of HALFEN GmbH is certified for the locations in Germany, France, the Netherlands, Austria, Poland, Switzerland and the Czech Republic according to ISO 9001:2015, Certificate No. 202384-2016-AQ-GER-DAkKS.

