

DECLARATION OF PERFORMANCE

CONF-DOP_BL-01-22

No. H-18-845-1/1

1.	Unique identification code of the product-type		HALFEN BL	
2.	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4)		HALFEN BL, BLQ see label on the packaging or product	
	Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:			
	Generic type and use		asymmetric masonry wall tie for horizontal connection of a wall to an anchor channel	
	Product size covered (anchor channels and corresponding screws)		BL-85, BL-120, BL-180, BLQ-85, BLQ-120, BLQ-180	
	For use in		Anchor channel HTA-CE 38/17	
	Anchor material / Screw material and intended use		HALFEN BL: - Stainless steel 1.4404 / 1.4571 acc. to EN 10088-2 - Steel S235 acc. to EN 10025-2 with zinc coat acc. to EN ISO 1461	
	Loading		Static and quasi static loading	
4.	Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5)		Leviat GmbH, Liebigstraße 14, 40764 Langenfeld, Germany	
5.	Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2)		-	
6.	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V		System 3 acc. to EN 845-1-2013	
7.	In case of the declaration of performance concerning a construction product covered by a harmonised standard		The notified testing laboratory ITB Katowice, ul. Korfantego 191, 40-153 Katowice European Notified Body No. 1488 performed the initial testing under system 3 and issued a test report No. LOK01-6024/13/R17OSK	
8.	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued		-	
9.	Declared performance			
	Essential Characteristics	Performance	Failure mode	Harmonized Technical Specification
	Max tension load with HTA-CE 38/17 and mortar class 5	3200 N (50 mm anchorage length)	mortar failure	EN 845-1:2013
	Displacement at 1/3 of the tension load	0,6 mm		
	Max shear load with standard joints and mortar class 5	2700 N (50 mm anchorage length)	mortar failure	
	Displacement at 1/3 of the shear load	0,9 mm		

DECLARATION OF PERFORMANCE

CONF-DOP_BL-01-22

No. H-18-845-1/1

9.	Compression load BL-180	1000 N	bending of the tie	EN 845-1:2013
	Displacement at 1/3 of the tension load	0,2 mm		
	Anchorage length in faced brickwork	min. 50 mm		
	Water repelling function	No resistance		
	Durability	Material code 1 or 11A		
	Dangerous substances	NDP		
	Where pursuant to Article 37 or 38 in the Specific Technical Documentation has been used, the requirements with which the product complies:		-	
10.	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.			
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.				

Langenfeld, 02.01.2022

Signed for and on behalf of the manufacturer by



Chris Oberli
(Managing Director | Europe Central)



Dr. Ing. Dirk Albartus
(Prokurist)